



InfiniBox[®]

Enterprise Storage that Scales, Learns and Evolves

The InfiniBox[®] enterprise storage array delivers faster-than-all-flash performance, high availability, and capacity density at multi-petabyte scale for mixed workloads. Zero-impact snapshots, synchronous/asynchronous replication, and data-at-rest encryption assure maximum data security and reliability. With InfiniBox, enterprise IT organizations and cloud service providers exceed their service level objectives while lowering the cost and complexity of their storage operations.

InfiniBox

HIGH AVAILABILITY AND RELIABILITY

InfiniBox's self-healing architecture, designed to deliver unmatched availability, combined with our patented InfiniRAID™ and predictive analysis, delivers seven nines (99.99999%) uptime and non-disruptive upgrades. The InfiniBox component redundancy design enables rapid recovery from any component failure without impacting performance.

HIGH PERFORMANCE

A truly innovative cache management algorithm combined with an ultra-efficient data layout (InfiniRaid™) delivers maximum performance at a fraction of the cost of all-flash arrays. High throughput, at sub-millisecond latency, is the key to high performance operation as well as powering synchronous and asynchronous replication for block and file.

MULTI-PETABYTE SCALE

Maximum system capacity utilization is possible due to extremely efficient thin provisioning, continuous space reclamation, and inline data compression. Packaged in a single 42U rack and scaling to well over 5PB or more effective capacity, multiple system consolidations are easy to accomplish and remarkably cost-effective.

BUSINESS AGILITY AND CONTINUITY

Space-efficient, low impact snapshots simplify data protection as well as accelerating agile development and quality assurance with nearly infinite copies of your data. Integrated synchronous and asynchronous replication provides the highest levels of data reliability for both onsite and offsite business continuity and disaster mitigation planning.

SIMPLE AND POWERFUL MANAGEMENT FOR MULTI-TENANT ENVIRONMENTS

An intuitive HTML5 GUI simplifies the most complex storage management operations. A comprehensive RESTful API and a powerful CLI help automate complex tasks, including policy management for Quality of Service. Easily facilitate service level coordination across tenants, workloads, and volumes. Monitor and measure all feature performance elements using InfiniMetrics.

UNIFIED STORAGE

InfiniBox concurrently provides FC, iSCSI and NFSv3 NAS protocols in a single, common platform managed through a single, simple and consistent management interface.

CONNECTIVITY AND INTEGRATION

InfiniBox integrates with the critical business applications in your datacenter using native interfaces. The InfiniBox ecosystem includes a rich solution portfolio for platforms such as virtualization, databases, backup & recovery, and more. Our fast and intuitive host connectivity and storage provisioning - Host PowerTools™ - reduces management tasks from days or hours to seconds!



InfiniBox Specifications

	F6000	F4000	F2000
Capacity			
Usable Capacity	1,035TB to 4,149TB	682TB to 1,366TB	248TB to 499TB
Effective Capacity*	2,070TB to 8,298TB	1,364TB to 2,732TB	496TB to 998TB
Performance Features			
Memory	Up to 3,072GB	Up to 2,304GB	Up to 768GB
Flash Cache	Up to 207TB	Up to 103TB	Up to 103TB
IOPS	1M IOPS	750,000 IOPS	500,000 IOPS
Throughput	12.5 GB/Sec	10 GB/Sec	7 GB/Sec
Connectivity and Integration			
FC Ports	24x 8Gbps		
Ethernet Ports	12x 10GbE		
Ecosystem Integration	VMware, OpenStack, CommVault, Veritas, Microsoft, SAP, Host PowerTools for Linux, UNIX, Windows		
Availability and Protection			
Fully Redundant Hardware	N+2 Redundant System Components Resilient Against Multiple Concurrent Failures Triple-Active Redundant Nodes		
Data Protection	Fastest Rebuild in the Industry In-Line and At-Rest Data-Verification Sync and Async Replication		
Scalability			
Max. Volume/File System Size	Unlimited		
Max. Files per Directory/File System	> 17B		
Max. Number of Volumes	Unlimited		
Max. Number of Snapshots	100,000		
Max. Number of File Systems	4,000		
Max. File Size	> 1PB		
Support	Three Years of 24 x 7 x 365 Maintenance — No Additional Cost		
Pricing and Licensing			
System Feature Licensing	All Features Included — No Additional Cost		

*Effective Capacity includes the benefits of thin provisioning, inline compression, and space-efficient snapshots

InfiniBox Physical and Environmental Characteristics

	F6000	F4000	F2000
Power Consumption	8KW	5.5KW	3.5KW
Form Factor	Standard 19" 42U Rack	26U in a Standard 19" 42U Rack	18U in a Standard 19" 42U Rack
Maximum Weight,	1,207 kg (2,661 lb)	835 kg (1,841 lb)	593 kg (1,308 lb)
Operating Temperature	10°C – 30°C (50°F – 85°F)		
Altitude (max)	3,050 m (10,000 ft)		
Humidity	25% – 80% non-condensing		
Service Clearance Front/Rear	120 cm / 45 cm (47.24 in / 17.8 in)		
Input Voltage	North America: Single-phase: 208V International: Single-phase: 220V		Three-phase: 208V between phases Three-phase: 380V between phases
Input Current	N. America: Single-phase: 4 inputs, 30A each Three-phase: 2 inputs, 3*30A each Int'l: Single-phase: 4 inputs, 32A each Three-phase: 2 inputs, 3*16A each		N. America: Single-phase: 2 inputs, 30A each Three-phase: 2 inputs, 3*30A each Int'l: Single-phase: 2 inputs, 32A each Three-phase: 2 inputs, 3*16A each
Input Power Frequency	50/60 HZ		
Cooling	27,500 BTU/Hour	18,800 BTU/Hour	12,000 BTU/Hour
Safety/EMC	Safety: EN 60950-1, CSA/UL 60950-1, IEC 60950-1 Ed 2 EMC: EN 55022 (CISPR 22), EN 55032 (CISPR 32), EN 55024 (CISPR 24), EN 61000-3-2, EN 61000-3-3, FCC Part 15, ICES-003 Issue 5		